

**Part Number: 83265**



50 Ohm Coax, RG178, 30 AWG Stranded SCCCS, SPC Braid, FEP Jacket, Commercial Non-QPL Product.

**Product Description**

RG-178/U, 30 AWG stranded (7x38) .012" silver-plated copper-covered steel conductor, TFE insulation, silver-plated copper braid shield (95% coverage), FEP jacket, commercial non-QPL product.

**Technical Specifications**

**Product Overview**

Environmental Space:	Outdoor - Aerial
----------------------	------------------

**Physical Characteristics (Overall)**

**Conductor**

AWG	Stranding	Material	Nominal Diameter	No. of Coax
30	Stranded	SCCCS - Silver Coated Copper Covered Steel	0.012 in	1

Conductor Count:	1
Conductor Size:	30 AWG

**Insulation**

Material	Material Trade Name	Nominal Diameter
TFE - Tetrafluoroethylene	Teflon®	0.033 in

**Outer Shield Material**

Type	Layer	Material	Coverage [%]
Braid	1	SPC - Silver Plated Copper	95 %

**Outer Jacket Material**

Material	Nominal Diameter
FEP - Fluorinated Ethylene Propylene	0.071 in

**Electrical Characteristics**

**Conductor DCR**

Nominal Conductor DCR	Nominal Outer Shield DCR	Outer Conductor DCR
244 Ohm/1000ft	14.6 Ohm/1000ft	14.6 Ohm/1000ft

**Capacitance**

Nom. Capacitance Conductor to Shield
29 pF/ft

**Inductance**

Nominal Inductance
0.072 µH/ft

**Impedance**

Nominal Characteristic Impedance
50 Ohm

**High Frequency (Nominal/Typical)**

Frequency [MHz]	Nom. Insertion Loss
1 MHz	2.6 dB/100ft
10 MHz	5.6 dB/100ft
50 MHz	10.5 dB/100ft
100 MHz	14 dB/100ft
200 MHz	19 dB/100ft
400 MHz	28 dB/100ft
700 MHz	37 dB/100ft
900 MHz	42.5 dB/100ft
1000 MHz	46 dB/100ft

#### Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.46 ns/ft	69.5 %

#### Power Rating

Frequency [MHz]	Max. Power Rating [W]	Nominal Power Rating [W]
50 MHz	380 W	380 W
100 MHz	253 W	253 W
200 MHz	170 W	170 W
400 MHz	113 W	113 W
700 MHz	81 W	81 W
900 MHz	70 W	70 W
1,000 MHz	66 W	66 W

#### Voltage

Description	Voltage Rating [V]
750V RMS	750 V RMS (Mil Spec)

#### VSWR

Frequency [MHz]	Max. VSWR
50 MHz - 1000 MHz	per M17/93-RG178

#### Temperature Range

Non-UL Temp Rating:	200°C
Operating Temp Range:	-70°C To +200°C

#### Mechanical Characteristics

Bulk Cable Weight:	5 lbs/1000ft
Max Recommended Pulling Tension:	12 lbs
Min Bend Radius/Minor Axis:	1 in

#### Standards

RG Type:	178/U Type
Military Specification:	Commercial, non-QPL product (M17/93-RG178)
QPL (Qualified Parts List):	No
Other Specification:	UL Style 1637

#### Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes

#### Suitability

Suitability - Aerial:	Yes - When supported by messenger wire
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	No

**Plenum/Non-Plenum**

Plenum (Y/N):	No
---------------	----

**Part Number**

**Variants**

Item #	Color	Footnote
83265 009100	White	E
83265 0091000	White	E
83265 009500	White	E

Footnote:	E - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'.
-----------	--

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.